

Established 1982



South Moorlan

Tree planting

This area is fair conservation va quickly.

Alder (Alnus glu Silver Birch (Be Rowan (Sorbus Field Maple (Ad Holly (Ilex aquit Wild Cherry (Pr Bird Cherry (Pr

I would plant th would have to

H. E. Williams

Hugh Williams Tree Heritage



| nd Consultants | |
|--|--|
| nds Leisure Centre, Cheadle, Staffordshi | ire |
| proposals for screening of new pavilion | off Thorley Drive |
| irly rural and I would suggest that you use navalue. The following will thrive in most soils a | native species with high and get established fairly |
| lutinosa) etula pendula or nigra) s aucuparia) ccer campestre) ifolium) runus avium) runus padus) | |
| nese as feathered stock 150-180 cms. high be much smaller as it does not transplant w | apart form the Holly which vell. |
| | |
| Ltd | |
| | |
| | |
| | |
| | |
| | |
| | |
| reet, Leek, Staffordshire, ST13 8DQ 22809 F: 01538 399812 om W:www.treeheritage.co.uk Leek, Staffordshire. Registered No. 1655803 VAT No. 368064436 | APPROVED CONTRACTOR |

CAR PARK & AMENITY LIGHTING

CLASSIQUE AL1000







Benefits

- High performance bollard with excellent light distribution
- Extensively tested for vandal resistance
- Highly versatile with a wide range of applications from parks to security

Features

- Die-cast aluminium head unit with clear polycarbonate outer tube
- Bollard shaft of steel CHS tube
- Bollard shaft and head unit castings are finished in black, textured polyester coating
- Louvred light controller of pressed aluminium satin finish
- Integral control gear
- Symmetrical lighting distribution
- Supplied for root mounting as standard, with the option of flange plate fixing
- Mounting height 0.87m

Applications

- General
- Parks and gardens
- Security
- Pedestrian areas


Access

Access the lamp and control gear by removing the head unit (secured by a single vandal-resistant screw and twist-lock mechanism)




| | Lamp wattage and type | Lamp holder | Description | Weight (Kg) | Windage [m²] |
|--------|---|-------------------|--------------------------------------|----------------|-----------------|
| AL1011 | 20/23W DULUX EL 50/80W HQL 50/70W SON-E | E27 E27 E27 | Bollard: satin louvres integral gear | n/a | n/a |

Key features



Mounting
Supplied for root mounting
as standard Flange plate
fixing available
Mounting height: 0.87m

All dimensions are in mm





This could work for you

To find out more visit: www.abacuslighting.com

