

Global Variables

Region	FSR - England & Wales
Return Period (yrs)	100
M5-60 (mm)	18.000
Ratio R	0.350
Volumetric Runoff Coef	0.840
Profile Type	Winter
PIMP (%)	100
Areal Reduction Factor	1.000
Storm Duration (mins)	1440
Hot Start (mins)	0
Hot Start Level (mm)	0
Manhole Headloss Coefficient	0.500
MADD Factor * 10m³/ha Storage	2.000
Foul Sewage/Hectare (l/s)	0.00
Additional Flow - % of Total Flow	0
Number of Input Hydrographs	0
Number of Time/Area Diagrams	0
Number of Bifurcations	0
Number of Overflows	0
Number of Off-Line Controls	1
Number of On-Line Controls	1

Starting Storm file name

C:\Leek\system 15-04-2010\System 6\proposed system 6.SWS

Freely Discharging Outfalls

Outfall Pipe Number	Outfall MH/No	C.Level (m)	I.Level (m)	D,L (mm)	B (mm)
1.002	headwall	154.000	152.700	1800	0


On-Line Controls (Hydro-Brake®)

US/PN	Volume (m³)	Ctrl MH Name	Invert (m)	Type	Dia (m)	D.Head (m)	D.Flow (l/s)	Headloss (m)	Flow (l/s)
1.001	1.414	3	152.942	Md4	0.132	1.000	13.6	0.2	10.7
								0.4	11.0
								0.6	10.8
								0.8	12.2
								1.0	13.6
								1.4	16.1
								1.8	18.2
								2.2	20.2
								2.6	21.9
								3.0	23.6
								3.4	25.1

Infiltration Systems

Warning:- Volume should always be included unless the upstream pipe is being used for storage and/or as a carrier.

DS/PN	MH Loss	Height above DS PN (m)	Filename	Type	Include Volume
1.002	0.500	0.000	cellular storage system 6.src	Cellular Storage	Yes (capped) (lvl 153.642m)


Denis Wilson Partnership		Page 4
Portland Tower Portland Street Manchester M1 3LF	Sainsbury's Leek Proposed Drainage System 6	
Date 20-04-10 File proposed system 6.SUM	Designed By A O'Neill Checked By	
Micro Drainage	Simulation W.11.2	

Network Details

* - Indicates pipe has been modified outside of WinDes's Storm/Foul & Schedules

PN	Length (m)	Fall (m)	Slope (1:x)	Area (ha)	T.E. (mins)	Rain Pro	k (mm)	Hyd Sect	Dia (mm)
1.000	12.43	0.058	214.3	0.223	5.00	1	0.600	o	750
1.001	5.00	0.130	38.5	2.500	0.00	1	0.600	o	750
1.002	15.58	0.242	64.4	0.000	0.00	1	0.600	o	450

PN	USMH No.	US/CL (m)	US/IL (m)	US C.Depth (m)	DS/CL (m)	DS/IL (m)	DS C.Depth (m)	Ctrl No.	US/MH (mm)
1.000	1	154.780	153.130	0.900	154.730	153.072	0.908		1800
1.001	2	154.730	153.072	0.908	155.900	152.942	2.208		1800
1.002	3	155.900	152.942	2.508	154.000	152.700	0.850	9	1800

Denis Wilson Partnership		Page 5
Portland Tower Portland Street Manchester M1 3LF	Sainsbury's Leek Proposed Drainage System 6	
Date 20-04-10 File proposed system 6.SUM	Designed By A O'Neill Checked By	
Micro Drainage	Simulation W.11.2	

PIPELINE SCHEDULES

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH No.	C.Level (m)	I.Level (m)	C.Depth (m)	MH DIAM., L*W (mm)
1.000	o	750	1	154.780	153.130	0.900	1800
1.001	o	750	2	154.730	153.072	0.908	1800
1.002	o	450	3	155.900	152.942	2.508	1800

Downstream Manhole

PN	Length (m)	Slope (1:x)	MH No.	C.Level (m)	I.Level (m)	C.Depth (m)	MH DIAM., L*W (mm)
1.000	12.43	214.3	2	154.730	153.072	0.908	1800
1.001	5.00	38.5	3	155.900	152.942	2.208	1800
1.002	15.58	64.4	headwall	154.000	152.700	0.850	1800

Design Audit Report

Filename	C:\Leek\system 15-04-2010\System 6\Design Audit Wizard\proposed system 6.SUM
Date Audited	20/04/10 16:59
Pipes Audited	3
Site Slope (1:x)	76.8
	15 Summer, 30 Summer, 60 Summer, 120 Summer, 240 Summer, 360 Summer, 480 Summer, 960 Summer, 1440 Summer, 2160 Summer, 2880 Summer, 4320 Summer, 15
Storms Used (mins)	Winter, 30 Winter, 60 Winter, 120 Winter, 240 Winter, 360 Winter, 480 Winter, 960 Winter, 1440 Winter, 2160 Winter, 2880 Winter, 4320 Winter

Audit	Failures	Status
Manhole Sizes	0	Passed
Surcharge	0	Passed
Flood	0	Passed
Storage	0	Passed
Pipe Diameters	0	Passed
Pipe Lengths	0	Passed
Coordinate Accuracy	0	Passed
Cover Levels	1	Failed
Backdrops	0	Passed
Full Bore Velocity	1	Failed
Proportional Velocity	1	Failed
Crossings / Clashes	0	Not Run
Manhole Headloss	0	Not Run
ICP Audit	0	Not Run

Manhole Size Audit

All Manhole Sizes comply with the manhole size file:
C:\Program Files\Micro Drainage Ltd\WinDes\STANDARD.MHS

Surcharge Audit


No pipes surcharge passed the 50 mm limit for the 30 year +0% climate change storm

Flood Audit

No pipes flood for the 100 year +30% climate change storm

Storage Audit

Storage Volume is at typical design values

Denis Wilson Partnership		Page 7
Portland Tower Portland Street Manchester M1 3LF	Sainsbury's Leek Proposed Drainage System 6	
Date 20-04-10 File proposed system 6.SUM	Designed By A O'Neill Checked By	
Micro Drainage	Simulation W.11.2	

Pipe Diameter Audit

All pipe diameters are => 150 mm

Pipe Length Audit

All pipe lengths are <= 100.00 m

Coordinate Accuracy Audit

All pipe lengths are within 1.000 m of coordinates

Cover Level Audit

The following pipes have Cover Depths outside of the range 0.900-6.000 m

PN	USIL (m)	USCL (m)	US Depth (m)	Dia (mm)	DSIL (m)	DSCL (m)	DS Depth (m)
1.002				450	152.700	154.000	0.850

Backdrop Audit

All backdrops are within the range 0.200-1.500m

Full Bore Velocity Audit

The following pipes have Full Bore Velocity outside of the range 1.00-3.00 m/s

PN	Vel (m/s)
1.001	4.52

Proportional Velocity Audit

The following pipes have Proportional Velocity outside of the range 1.00-3.00 m/s for the 1 year +0% climate change storm

PN	Storm (mins)	Vel (m/s)
1.000	15 Summer	0.26

Crossings / Clashes Audit

The Crossings / Clashes Audit was not completed by user request

Manhole Headloss Audit

The Manhole Headloss Audit was not completed by user request

Interim Code of Practice Audit

The ICP Audit was not completed by user request

Rainfall Hyetograph

Region	FSR - England & Wales
Return Period (yrs)	100
M5-60 (mm)	18.000
Ratio R	0.350
Profile Type	Winter
Storm Duration (mins)	1440

Time (mins)	Rain (mm/hr)	Time (mins)	Rain (mm/hr)	Time (mins)	Rain (mm/hr)	Time (mins)	Rain (mm/hr)
24	0.25	384	2.32	744	8.72	1104	2.05
48	0.71	408	2.62	768	8.48	1128	1.86
72	1.05	432	2.96	792	8.14	1152	1.72
96	1.30	456	3.41	816	7.66	1176	1.62
120	1.43	480	3.87	840	7.17	1200	1.57
144	1.51	504	4.35	864	6.65	1224	1.55
168	1.54	528	4.94	888	6.03	1248	1.54
192	1.55	552	5.48	912	5.48	1272	1.55
216	1.54	576	6.03	936	4.94	1296	1.54
240	1.55	600	6.65	960	4.35	1320	1.51
264	1.57	624	7.17	984	3.87	1344	1.43
288	1.62	648	7.66	1008	3.41	1368	1.30
312	1.72	672	8.14	1032	2.96	1392	1.05
336	1.86	696	8.48	1056	2.62	1416	0.71
360	2.05	720	8.72	1080	2.32	1440	0.25