# Ashmore




A single lap, interlocking double plain tile, with the engineered precision and ease of installation of an interlocking tile.

## Colour availability

**Key** (S) Smooth finish










## Technical data

| | | |
|---|---|---|
| Size of slate | 267mm x 333mm | |
| Minimum pitch* | 25° (77mm headlap) | 22.5° (92mm headlap) |
| Maximum pitch | 90° | |
| Minimum headlap | 77mm | |
| Maximum gauge | 190mm | |
| Tile thickness | 16mm (nominal) | |
| Cover width | 302mm (nominal) | |
| Hanging length | 235mm (nominal) | |
| Covering capacity (net) | 17.5 tiles/m² at 77mm headlap | 19 tiles/m² at 92mm headlap |
| Weight of tiling (approx.) | 48kg/m² (0.47 kN/m²) at 77mm headlap | 52kg/m² (0.51 kN/m²) at 92mm headlap |
| Battens required (net) | 5.3 lin.m/m² at 77mm headlap | 5.8 lin.m/m² at 92mm headlap |
| Batten size recommended | 38 x 25mm for rafters/supports not exceeding 450mm centres (fixed to BS 5534)<br>50 x 25mm for rafters/supports not exceeding 600mm centres (fixed to BS 5534) | |
| Tile nails | 45mm x 3.35mm | |
| Fixing clips | Eaves, verge and tile clips | |
| Authority | BS EN 490 | |

* The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.

## Sustainability

- ✓ A+ rated in the BRE Green Guide (based on generic rating for UK produced concrete interlocking tiles Element Refs: 812410007, 812410018, 812410049)
- ✓ BES 6001 (Responsible Sourcing) certified
- ✓ Independent carbon footprint certification

## Ashmore fittings

Available in all colours to match main tiles.

Ashmore tiles should be laid broken bond. The required broken bond pattern is created by the introduction of three-quarter width tiles in alternate courses. Tile-and-a half tiles are available for use at hips and valleys.




Ashmore three quarter tile (LH)




Ashmore three quarter tile (RH)




Ashmore tile-and-a-half