

Y Series VRF

(22.4-45kW)

Heat Pump Outdoor Unit (Heating or Cooling)

CITY MULTI

VRF technology provides a simple and flexible solution where there is a demand for a changeover capability between heating and cooling for all indoor units, helping to ensure a constant and comfortable indoor climate.



next
GENERATION VRF

Key Features & Benefits:

- Effective, efficient solution meeting all the market needs
- Delivers the highest levels of comfort, both thermally and acoustically
- Cost effective delivery



Air Conditioning Product Information

Y Series VRF

(22.4-45kW)

Heat Pump Outdoor Unit (Heating or Cooling)



OUTDOOR UNITS		PUHY-P200YNW-A1	PUHY-P250YNW-A1	PUHY-P300YNW-A1	PUHY-P350YNW-A1	PUHY-P400YNW-A1	PUHY-P400YSNW-A1
CAPACITY (kW)	Heating (nominal)	25.0	31.5	37.5	45.0	50.0	50.0
	Cooling (nominal)	22.4	28.0	33.5	40.0	45.0	45.0
	High Performance Heating (UK)	25.0	31.5	35.6	42.8	45.0	50.0
	COP Priority Heating (UK)	22.8	28.7	34.1	41.0	43.0	45.5
	Cooling (UK)	20.1	25.1	30.0	35.8	40.3	40.3
POWER INPUT (kW)	Heating (nominal)	5.10	7.20	8.46	10.39	12.37	10.52
	Cooling (nominal)	4.81	7.14	8.79	10.95	14.19	9.97
	High Performance Heating (UK)	6.43	9.07	11.25	13.82	13.98	13.47
	COP Priority Heating (UK)	5.10	7.20	8.46	10.39	12.00	10.52
	Cooling (UK)	2.79	4.14	5.10	6.35	9.08	5.78
COP / EER (nominal)		4.90 / 4.65	4.37 / 3.92	4.43 / 3.81	4.33 / 3.65	4.04 / 3.17	4.75 / 4.51
MAX NO. OF CONNECTABLE INDOOR UNITS		17	21	26	30	34	34
MAX CONNECTABLE CAPACITY		50~130% OU Capacity	50~130% OU Capacity	50~130% OU Capacity	50~130% OU Capacity	50~130% OU Capacity	50~130% OU Capacity
AIRFLOW (m³/min)	High	170	185	240	270	300	170 / 170
	Gas	22.2 (7/8")	22.2 (7/8")	22.2 (7/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")
PIPE SIZE mm (in)	Liquid	9.52 (3/8")	9.52 (3/8") ¹	9.52 (3/8") ¹	12.7 (1/2")	12.7 (1/2")	12.7 (1/2")
	Heating / Cooling	59.0 / 58.0	61.0 / 60.0	64.5 / 61.0	64.0 / 62.0	67.0 / 65.0	62.0 / 61.0
SOUND PRESSURE LEVEL (dBA)		77.0 / 75.0	80.0 / 78.0	84.0 / 80.0	83.0 / 80.0	86.0 / 82.0	80.0 / 78.0
WEIGHT (kg)	Heating / Cooling	213	213	226	277	277	213 + 213
	Heating / Cooling	213	213	226	277	277	213 + 213
DIMENSIONS (mm)	Width	920	920	920	1240	1240	920 + 920
	Depth	740	740	740	740	740	740
	Height	1858	1858	1858	1858	1858	1858
	(1650mm without legs)	1858	1858	1858	1858	1858	1858
ELECTRICAL SUPPLY*2		380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz
PHASE*2		Three	Three	Three	Three	Three	Three
STARTING CURRENT (A)*2		8	8	8	8	8	8
NOMINAL SYSTEM RUNNING CURRENT (A)*2		8.1 / 7.7 [16.1]	11.5 / 11.4 [17.8]	13.5 / 14.0 [22.7]	16.6 / 17.5 [26.4]	19.8 / 22.7 [31.9]	16.8 / 15.9 [16.1]
GUARANTEED OPERATING RANGE (°C)		-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52
FUSE RATING (MCB sizes BS EN 60947-2) - (A)*2		1 x 20	1 x 20	1 x 25	1 x 32	1 x 32	1 x 20 / 1 x 20
MAINS CABLE No. Cores*2		4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth / 4 + earth
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (T) R410A (GWP 2088)		6.5 / 13.6	6.5 / 13.6	6.5 / 13.6	9.8 / 20.5	9.8 / 20.5	13 / 27.1
MAX ADDITIONAL REFRIGERANT (Kg) / CO ₂ EQUIVALENT (T) R410A (GWP 2088)		15.9 / 33.2	22.9 / 47.8	23.4 / 48.9	24 / 50.1	24.4 / 51.0	32 / 66.8


Notes: *SEER/SCOP available separately in the 'City Multi VRF Seasonal Efficiency' document. Based on Ecodesign Lot 21/6 to EN14825 standard.

*1 12.7mm(1/2") if P250 furthest length ≥ 90m, P300 furthest length ≥ 40m. *2 A separate power supply is required for each module. Where more than one figure is quoted there are multiple modules.

PUHY-P200/250/300YNW-A1 DIMENSIONS			PUHY-P350/400YNW-A1 DIMENSIONS			PUHY-P400YSNW-A1 DIMENSIONS		
SIDE VIEW	FRONT VIEW	UPPER VIEW	SIDE VIEW	FRONT VIEW	UPPER VIEW	SIDE VIEW	FRONT VIEW	UPPER VIEW



Telephone: 01707 282880
email: air.conditioning@meuk.mee.co.uk
les.mitsubishielectric.co.uk



UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880 Fax: 01707 278881
IRELAND Mitsubishi Electric Europe, Westgate Business Park, Ballymount, Dublin 24, Ireland. Telephone: (01) 419 8800 Fax: (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2020. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP:2088), R32 (GWP:675), R407C (GWP:1774), R134a (GWP:1430), R513A (GWP:631), R454B (GWP:466), R1234ze (GWP:7) or R1234yf (GWP:4). *These GWP values are based on Regulation (EU) No 517/2014 from IPCC 4th edition. In case of Regulation (EU) No.626/2011 from IPCC 3rd edition, these are as follows. R410A (GWP:1975), R32 (GWP:550), R407C (GWP:1650) or R134a (GWP:1300).

Effective as of May 2020

