

APPLICATION: DET/2021/0032

APPLICANT NAME:

Mr and Mrs J and S Gould

APPLICANT ADDRESS:

Lane End Farm
Morridge Side, Bradnop
Nr. Leek
Staffs
ST13 7HA

To whom it may concern,

Following approval of application DET/2021/0032, we are required to submit information to discharge a number of conditions.

Condition 4: Details of windows and doors.

All windows will be Residence 9 and coloured Painswick (Alternative names – Agate grey / RAL 7038). The joints are butted together to give an authentic timber appearance. All doors are also going to be coloured Painswick, and will be constructed as per the elevation drawings supplied with the application. The page from the brochure below shows the colour and the flush sash exterior appearance, along with the joints which give the effect of wooden windows.




Condition 6: Rooflight details.

As required by the condition, conservation rooflights manufactured by Velux are going to be installed. Windows from this range have the black exterior and vertical glazing bar as required by the condition. All 5 rooflights are going to be top hung and measure 55cm x 98cm.



Roof pitch



*The window is suitable for roof pitches between 15°-55°, also suitable for roof pitches between 55° and 75° with special springs. Please specify when ordering.

Interior finish options



White painted

Bright white finish for modern interiors

Glazing options

	Double glazing --70
Rain noise reduction	✓
Safety lamination	✓
Toughened glass	✓
UV filter	✓
Easy to clean	
Anti-dew	
Thermal transmittance of glazing (U _g -value)	1.0

Conservation

Conservation roof windows with glazing bar

Conservation roof windows are the perfect choice when planning dictates that a window of traditional external appearance is required. Its black exterior profiles and glazing bar blend seamlessly into the roof and match the original look of the building. It has the same technical features as a standard VELUX roof window.

- Available in both centre-pivot and top-hung
- RAL colour 9005

External frame sizes (wxh) cm	U _g -value W/m² K	CK04 55x98	CK06 55x118	FK06 66x118	MK06 78x118	MK08 78x140	UK04 134x98

Centre-pivot white painted							
GGL SD5N2	GGL 2570 roof window + EDN recessed flashing for slate up to 8mm thick (min 20°)	1.3	547	568	628	662	828
GGL SD5P2	GGL 2570 roof window + EDP flashing for plain tiles up to 14mm thick (min 25°)	1.3	487	505	560	592	744
GGL SD5W2	GGL 2570 roof window + EDW flashing for tiles up to 120mm in profile (min 15°)	1.3	487	505	560	592	744
GGL SD5J2	GGL 2570 roof window + EDJ recessed flashing for tiles up to 90mm in profile (min 20°)	1.3	547	568	628	662	828
Top-hung white painted							
GPL SD5N2	GPL 2570 roof window + EDN recessed flashing for slate up to 8mm thick (min 20°)	1.3	-	-	-	865	-
GPL SD5P2	GPL 2570 roof window + EDP flashing for plain tiles up to 14mm thick (min 25°)	1.3	-	-	-	791	-
GPL SD5W2	GPL 2570 roof window + EDW flashing for tiles up to 120mm in profile (min 15°)	1.3	-	-	-	791	-
GPL SD5J2	GPL 2570 roof window + EDJ recessed flashing for tiles up to 90mm in profile (min 20°)	1.3	-	-	-	865	-

Condition 10: Parking and turning areas.

