

GEOPHYSICAL SURVEY REPORT

Augustus Way, Cheadle

Client

Orion Heritage

Survey Report

28652

OASIS Ref. No.

Sumogeop1-544112

Date

21 July 2026



Survey Report 28652: Augustus Way, Cheadle

Survey dates	08 - 09 July 2026
Field co-ordinator	Liam Brice-Bateman BA
Field team	Angus Ritchie BA (Hons)
Report date	21 July 2026
Report author	Rebecca Fradgley BSc (Hons) ACIfA
CAD Illustrations	Rebecca Fradgley BSc (Hons) ACIfA
Project manager	Rebecca Fradgley BSc (Hons) ACIfA
Office	Eckington
Report approved	Dr John Gater BSc DSc(Hon) MCIfA FSA

SUMO GeoSurveys

Deer Park Business Centre, Eckington, Pershore, WR10 3DN
01684 592266

Aycliffe Business Park, Newton Aycliffe, DL5 6AU
01325 311 751

www.sumoservices.com
geophysics@sumoservices.com

SUMO GeoSurveys is a trading name of **SUMO Geophysics Ltd.**

TABLE OF CONTENTS

1	EXECUTIVE SUMMARY	1
2	PROJECT BACKGROUND.....	1
2.1	Site details	1
2.2	Archaeological context.....	1
2.3	Aims and objectives	2
3	SURVEY METHODOLOGY AND DATA PROCESSING.....	2
3.1	Instrumentation	2
3.2	Survey methodology	2
3.3	Data processing and display.....	2
4	RESULTS.....	3
4.1	Probable / Possible Archaeology.....	3
4.2	Ridge and Furrow	3
4.3	Uncertain.....	3
4.4	Former Field Boundary - Corroborated	3
4.5	Natural	3
4.6	Ferrous / Fired / Magnetic Disturbance	3
5	DATA APPRAISAL AND CONFIDENCE ASSESSMENT	4
6	CONCLUSION	4
7	BIBLIOGRAPHY AND REFERENCES	5
8	ARCHIVE	5
9	COPYRIGHT	5

Appendix A Technical information: Magnetic survey

Appendix B Technical information: Magnetic theory

Appendix C OASIS Data collection sheet

Appendix D Data management plan & archive selection strategy

LIST OF FIGURES

Figure 01	Various	Site Location
Figure 02	1:1500	Magnetic Gradient Data - Greyscale Plots
Figure 03	1:1500	Magnetic Gradient Data - Interpretation
Figure 04	NTS	Greyscale Plots / Interpretation / c. 1830s-1880s Ordnance Survey Map / 2020 Aerial Image
Figure 05	1:1500	Minimally Processed Magnetic Gradient Data - Greyscale Plots
Figure 06	1:1500	Magnetic Gradient Data - X-Y Trace Plots (Clipped At +/- 15nt)

The geophysical interpretation drawings must be used in conjunction with the relevant results section and appendices of this report.

1 EXECUTIVE SUMMARY

1.1 **SUMO GeoSurveys** was commissioned to undertake a geophysical survey of an area outlined for residential development. This survey forms part of an archaeological investigation being undertaken by **Orion Heritage**.

1.2 The survey at Cheadle has not identified any anomalies of definite archaeological interest, apart from former ridge and furrow cultivation. Several responses of uncertain origin have been mapped, including discrete zones of magnetic disturbance which may reflect former quarrying activity. An old field boundary and areas of natural magnetic variations are also visible in the results.

2 PROJECT BACKGROUND

2.1 *Site details*

NGR / Postcode	SK 01835 42726 / ST10 1FS			
Location	The survey area is located approximately 13km southeast of Stoke-on-Trent, at the east of Cheadle, Staffordshire. Augustus Way lies immediately north of the site, with agricultural land to the south and east and Thorley Drive Recreation Ground to the west.			
HER	Staffordshire			
OASIS Ref. No.	Sumogeop1-544112			
District	Staffordshire Moorlands			
Parish	Cheadle			
Topography	Sloping downwards from east to west			
Land use	Pasture			
Geology (BGS 2026)	Bedrock:	Pennine Lower Coal Measures Formation - mudstone, siltstone and sandstone;		
		Penning Lower Coal Measures Formation - sandstone.		
	Superficial:	None recorded.		
Soils (CU 2026)	Soilscape 17: slowly permeable seasonally wet acid loamy and clayey soils.			
Survey method(s)	Magnetometer survey (fluxgate gradiometer)			
Site area	6.3 ha - approximately 0.6 ha could not be surveyed due to long grass / vegetation.			

2.2 *Archaeological context*

2.2.1 An archaeological desk-based assessment was not available at the time of writing this report. Consultation comments from the Historic Environment Team at Staffordshire County Council (SCC 2026) indicates that the landscape around the site may have been farmed in the open field system by the 10th century and the Staffordshire HER records ridge and furrow across the site, which would suggest that it lay within Cheadle's agricultural hinterland during the early medieval period, medieval and post-medieval periods. An archaeological evaluation to the immediate north of the site found no significant archaeological features but did reveal C19th quarrying which would have truncated any below-ground remains.

2.3 ***Aims and objectives***

- 2.3.1 To locate and characterise any anomalies of possible archaeological interest within the study area.

3 **SURVEY METHODOLOGY AND DATA PROCESSING**

A magnetic survey was employed as the most effective method of locating the type of archaeological anomalies which might be expected at this site.

The survey fieldwork and this report follow the general guidance set out by ClfA (2020) and the European Archaeology Council (EAC) (2016).

3.1 ***Instrumentation***

- 3.1.1 The magnetic survey was undertaken using the following equipment configuration:

Sensors	Equipment configuration	Traverse interval (m)	Sample interval (m)
4 No. Bartington Grad 601	Cart-based system Hand pushed Data is georeferenced by RTK GNSS	1.0	0.25

3.2 ***Survey methodology***

- 3.2.1 The cart-based system can be towed by an all-terrain vehicle (ATV) or pushed by hand, depending on the ground conditions, accessibility and size of fields. The hand-pushed system was used in this instance.
- 3.2.2 The cart is fitted with a GNSS guidance system which is used to align the survey profiles and direct the operator.
- 3.2.3 The survey profiles are usually offset from field boundaries, buildings and other metallic features by several metres to reduce the detrimental effect that these surface magnetic features have on the data. Gaps were also left adjacent to boundaries and surface obstructions to allow the ATV and cart-based system sufficient space to safely pass and turn.
- 3.2.4 The location of the cart-based survey data is converted directly to Ordnance Survey National Grid co-ordinates, using the UK OSTN15 transformation.

3.3 ***Data processing and display***

- 3.3.1 The only processes performed on data are the following unless specifically stated otherwise:

Zero Mean Traverse: This process sets the background mean of each traverse within each grid to zero. The operation removes instrument striping effects and edge discontinuities over the whole of the data set.

- 3.3.2 The data was stored direct to a laptop using ML-GRAD software. Processing is carried out using Anomaly GeoSurveys which automatically corrects for instrument drift and calculates a mean value for each profile. A positional value is assigned to each data point based on

the sensor number and recorded GNSS co-ordinates. The data is gridded, and parameters are set based on the sensor spacing and mean values. No additional processing is required.

3.3.3 Greyscale raster images (PNG files) are displayed at a range of -1nT to 2nT, which is 'standard' for archaeological surveys. A colour plot is displayed at range of +/-100nT which

3.3.4 X-Y trace plots are examined for all the data and overlain onto the greyscale plot to assist in the interpretation, primarily to help identify dipolar / bipolar responses (that will probably be associated with surface / near-surface iron objects) and thermoremanent material. When not displayed in the report, a digital drawing showing the X-Y trace plot is provided in the Archive.

3.3.5 A detailed discussion of data processing, display and the general categories of anomaly which have been identified by the survey is provided in the Appendices.

4 RESULTS

The survey has been divided into four survey areas (Areas 1-4).

4.1 *Probable / Possible Archaeology*

4.1.1 No magnetic responses have been recorded that could be interpreted as being of definite archaeological interest, apart from former ridge and furrow (see 4.2.1 below).

4.2 *Ridge and Furrow*

4.2.1 A series of linear, roughly parallel, trends have been detected orientated from north-east to south-west and north-south in the results and they reflect former ridge and furrow cultivation.

4.3 *Uncertain*

4.3.1 Several discrete areas of moderate strength response are mapped in the data, predominantly in Area 4. They have been assigned to the category of *Uncertain* as they generally lack the defined morphology of anomalies that would usually be interpreted as being of archaeological interest. Given that C19th century quarrying was identified immediately to the north of the site, it is feasible that they reflect infilled quarry pits, although their exact origin remains unclear.

4.3.2 Other weak linear trends and a linear response running down the west of Area 1 also have an uncertain origin and could be a result of agricultural or natural processes.

4.4 *Former Field Boundary - Corroborated*

4.4.1 A linear anomaly can be seen running along the western boundary of Area 1 and can be corroborated with the line of a former field boundary, visible on available historic OS maps (Fig. 04).

4.5 *Natural*

4.5.1 Amorphous and discrete areas of increased magnetic response are present in the results which are of natural origin, i.e. reflecting localised variations in the underlying geology. It is noted that the small discrete responses are typical of 'pitting' which is common on sandstone geologies.

4.6 *Ferrous / Fired / Magnetic Disturbance*

4.6.1 Smaller scale ferrous anomalies ("iron spikes") are present throughout the data and are characteristic of small pieces of ferrous debris in the topsoil. Some fired material (brick / tile) can produce similar responses as can gravels derived from igneous rocks. These types of responses are commonly assigned a modern origin, unless there is strong supporting evidence indicating a different cause. Where isolated responses are grouped together, they are usually categorised as magnetic disturbance and indicate the presence of a

concentration of (usually modern) material. Only the most prominent of these are isolated responses and areas of magnetic disturbance are highlighted on the interpretation diagram.

- 4.6.2 Ferrous responses close to field boundaries are usually due to adjacent fences and gates.

5 DATA APPRAISAL AND CONFIDENCE ASSESSMENT

- 5.1** The results from this survey indicate the presence of former ridge and furrow plus anomalies of uncertain origin; consequently, the technique is deemed to have been effective.

- 5.2** It should be noted that a geophysical survey does not directly locate sub-surface features - it identifies variations or anomalies in the background response caused by features. The interpretation of geophysical anomalies is often subjective, and it is rarely possible to identify the cause of all such anomalies. Not all features will produce a measurable anomaly, and the effectiveness of a geophysical survey is also dependant on the site-specific conditions. The main factors that may limit whether a feature can be detected are the composition of a feature, its depth and size and the surrounding material. It is not possible to guarantee that a geophysical survey will identify all sub-surface features.

6 CONCLUSION

- 6.1** The magnetometer survey has not recorded any magnetic responses that could be interpreted as being of definite archaeological interest, apart from former ridge and furrow cultivation. Discrete zones of increased magnetic response could reflect former quarrying activity, given that similar features were recorded immediately to the north. A former field boundary has been identified, while other anomalies of uncertain origin could be agricultural or natural. Other natural variations are also present in the results.

7 BIBLIOGRAPHY AND REFERENCES


- BGS 2026 *Geology of Britain Viewer*; British Geological Survey. Website: <http://www.bgs.ac.uk/opengeoscience/home.html?Accordion1=1#maps>
- ClfA 2020 *Standard and guidance for archaeological geophysical survey*; ClfA guidance note 2014 (amended 2020). Chartered Institute for Archaeologists, Reading <https://www.archaeologists.net/sites/default/files/2023-11/ClfA-SandG-Geophysical-Survey-2020.pdf>
- CU 2026 *Soilscapes Viewer*; LandIS: The Land Information System. Soil data for England and Wales. Website: <https://www.landis.org.uk/soilscapes/>
- EAC 2016 *EAC Guidelines for the Use of Geophysics in Archaeology*; European Archaeological Council, Guidelines 2.
- SCC 2026 *Staffordshire County Council Historic Environment Team response on historic environment for Land at Augustus Way, Cheadle*. Ref. HoEC/EC3210/SS/LP/ CST10868

8 ARCHIVE

- 8.1.1 The minimally processed data, data images, X-Y traces and a copy of this report are stored in **SUMO GeoSurveys'** digital archive, on an internal RAID configured NAS drive in the Eckington Office. These data are also backed up to the Cloud for off-site storage.
- 8.1.2 The Grey Literature will be archived with OASIS and the relevant HER within a period of 12 months.

9 COPYRIGHT



- 9.1.1 All copyright and intellectual property rights in this report, including all drawings, figures, and data, remain the property of SUMO Geophysics Ltd and may not be used, reproduced, or distributed without prior written permission.
- 9.1.2 This report may contain material that is subject to third-party copyright (including, but not limited to, Ordnance Survey © Crown Copyright) or other intellectual property rights. Such material is reproduced under licence for the purposes of this report only and remains the property of the respective rights holders; SUMO Geophysics Ltd cannot transfer these rights.



NTS



SK



NTS

NOTES

- SUMO GeoSurveys cannot accept responsibility for the reliability or accuracy of any information provided by a third party.
- This drawing and the information contained therein is issued in confidence and is the copyright of SUMO GeoSurveys. Disclosure of this information to third parties and unauthorised copying or replication of this data without approval is forbidden.

KEY

	Site boundary
	Survey area
	Unsurveyable




Title: Site Location	
Client: Orion Heritage	
Project: SUMO-28652: Augustus Way, Cheadle	
Scale: AS SHOWN	Fig No: 01



NOTES

1. The Ordnance Survey co-ordinates obtained for this survey were measured using the UK OSTN15 transformation. This transformation should be taken into account if the survey data is relocated.
2. SUMO GeoSurveys cannot accept responsibility for the reliability or accuracy of any information provided by a third party.
3. This drawing and the information contained therein is issued in confidence and is the copyright of SUMO GeoSurveys. Disclosure of this information to third parties and unauthorised copying or replication of this data without approval is forbidden.




Title: Magnetic Gradient Data - Greyscale Plots	
Client: Orion Heritage	
Project: SUMO-28652: Augustus Way, Cheadle	
Scale: 1:1500@A3 	Fig No: 02



NOTES

1. The Ordnance Survey co-ordinates obtained for this survey were measured using the UK OSTN15 transformation. This transformation should be taken into account if the survey data is relocated.
2. SUMO GeoSurveys cannot accept responsibility for the reliability or accuracy of any information provided by a third party.
3. This drawing and the information contained therein is issued in confidence and is the copyright of SUMO GeoSurveys. Disclosure of this information to third parties and unauthorised copying or replication of this data without approval is forbidden.



Title: Magnetic Gradient Data - Colour Plots

Client: Orion Heritage

Project: SUMO-28652: Augustus Way, Cheadle




Fig No: 03



NOTES

- 1. The Ordnance Survey co-ordinates obtained for this survey were measured using the UK OSTN15 transformation. This transformation should be taken into account if the survey data is relocated.
- 2. SUMO GeoSurveys cannot accept responsibility for the reliability or accuracy of any information provided by a third party.
- 3. This drawing and the information contained therein is issued in confidence and is the copyright of SUMO GeoSurveys. Disclosure of this information to third parties and unauthorised copying or replication of this data without approval is forbidden.


KEY

	Ridge and furrow
	Uncertain origin (discrete anomaly / trend / increased response)
	Former field boundary (corroborated)
	Natural (e.g. geological / pedological)
	Ferrous and / or fired material




Title:	Magnetic Gradient Data - Interpretation
Client:	Orion Heritage
Project:	SUMO-28652: Augustus Way, Cheadle

Scale: 1:1500@A3	Fig No:
	04



- ### NOTES
1. The Ordnance Survey co-ordinates obtained for this survey were measured using the UK OSTN15 transformation. This transformation should be taken into account if the survey data is relocated.
 2. SUMO GeoSurveys cannot accept responsibility for the reliability or accuracy of any information provided by a third party.
 3. This drawing and the information contained therein is issued in confidence and is the copyright of SUMO GeoSurveys. Disclosure of this information to third parties and unauthorised copying or replication of this data without approval is forbidden.



KEY	
	Ridge and furrow
	Uncertain origin (discrete anomaly / trend / increased response)
	Former field boundary (corroborated)
	Natural (e.g. geological / pedological)
	Ferrous and / or fired material

Title:
Greyscale Plot / Interpretation / c. 1830s-1880s
Ordnance Survey Map / 2020 Aerial Image

Client:
Orion Heritage


Project:
SUMO-28652: Augustus Way, Cheadle

Scale: NOT TO SCALE	Fig No: 05
------------------------	---------------



NOTES

- 1. The Ordnance Survey co-ordinates obtained for this survey were measured using the UK OSTN15 transformation. This transformation should be taken into account if the survey data is relocated.
- 2. SUMO GeoSurveys cannot accept responsibility for the reliability or accuracy of any information provided by a third party.
- 3. This drawing and the information contained therein is issued in confidence and is the copyright of SUMO GeoSurveys. Disclosure of this information to third parties and unauthorised copying or replication of this data without approval is forbidden.



Title: Minimally Processed Magnetic Gradient Data - Greyscale Plots

Client: Orion Heritage

Project: SUMO-28652: Augustus Way, Cheadle

Scale: 1:1000@A3 meters 0 75 Fig No: 06



NOTES

1. The Ordnance Survey co-ordinates obtained for this survey were measured using the UK OSTN15 transformation. This transformation should be taken into account if the survey data is relocated.
2. SUMO GeoSurveys cannot accept responsibility for the reliability or accuracy of any information provided by a third party.
3. This drawing and the information contained therein is issued in confidence and is the copyright of SUMO GeoSurveys. Disclosure of this information to third parties and unauthorised copying or replication of this data without approval is forbidden.



Title: Magnetic Gradient Data - X-Y Trace Plots (clipped at +/-15nT)	
Client: Orion Heritage	
Project: SUMO-28652: Augustus Way, Cheadle	
Scale: 1:1500@A3 	Fig No: 07

Appendix A - Technical information: Magnetic survey

Instrumentation:

Fluxgate gradiometers were used for the magnetic survey. These are systems that have two fluxgate magnetometers a set distance apart in a vertical sensor each of which measures the vertical component of the earth's magnetic field. The difference in measurements between the two magnetometers indicates the gradient of the earth's magnetic field.

Generally, features up to 1 m deep may be detected using fluxgate gradiometers, though strongly magnetic objects may be visible at greater depths and features / material that produce relatively weak magnetic responses may only be detected at shallower depths.

Data points and survey grids are georeferenced using using an RTK GNSS (Real-Time Kinematic Global Navigation Satellite System) to an accuracy usually in the order of +/- 0.05 m, and at all times better than 0.1 m. Positional data is converted to the Ordnance Survey National Grid co-ordinates, using the UK OSTN15 transformation.

SUMO GeoSurveys utilise Bartington or Foerster fluxgate gradiometers in several different configurations, depending on the client's requirements, survey objectives and site specific conditions. These include:

Bartington cart system

Cart survey: Four Grad601 sensors, with a sensor spacing of 1.0 m, are mounted on a non-magnetic cart. Readings are taken at nominal 0.125 m intervals. The sensors and an on-board RTK GNSS are connected to a control unit / data logger which allows each data point to be geo-referenced and related to Ordnance Survey National Grid. Readings are triggered at time intervals so the speed of survey can affect how often a reading is taken but the frequency a reading is taken and the speed of survey are set so that on average a reading will be taken at the required interval or better.

Bartington Grad 601-2

Hand-held: In this configuration two paired sensors, connected to a control unit / data logger, are carried by hand. The sensor are spaced 1 m apart and readings are taken at 0.25 m centres along traverses. Regular 30 m grids are set out across the survey area and the data is collected over these.

Foerster cart system (MACS)

Cart survey: A multi-sensor array cart system (MACS) utilising 4 or 8 Foerster 4.032 Ferex CON 650 gradiometers that are mounted on a non-magnetic cart. Readings are taken at between 0.1 and 0.15 m intervals. The sensors and an on-board RTK GNSS are connected to a control unit / data logger (an Eastern Atlas digitiser) which allows each data point to be geo-referenced and related to Ordnance Survey National Grid. Readings are triggered at time intervals so the speed of survey can affect how often a reading is taken but the frequency a reading is taken and the speed of survey are set so that on average a reading will be taken at the required interval or better.

Foerster cart system (MACS)

Cart survey: A multi-sensor array cart system (MACS) utilising 4 Foerster 4.032 Ferex MG-10-550 gradiometers that are mounted on a non-magnetic cart. Readings are taken at between 0.1 and 0.15 m intervals. The sensors and an on-board RTK GNSS are connected to a control unit / data logger which allows each data point to be geo-referenced and related to Ordnance Survey National Grid. Readings are triggered at time intervals so the speed of survey can affect how often a reading is taken but the frequency a reading is taken and the speed of survey are set so that on average a reading will be taken at the required interval or better.

Data processing

The processing sequence used for the data will depend on the instrument and configuration used.

Bartington Grad601 cart survey data

Zero Mean	This process sets the background mean of each traverse to zero. The operation
Traverse	removes striping effects and edge discontinuities caused by individual sensors having slightly different values when zeroed or where striping errors occur due to instrument drift or are a product of data collection.

Bartington Grad601-2 hand-held data

Zero Mean	This process sets the background mean of each traverse within each grid to zero.
Traverse	The operation removes striping effects and edge discontinuities caused by individual sensors having slightly different values when zeroed or where striping errors occur due to instrument drift or are a product of data collection.
Step Correction (De-stagger)	When gradiometer data are collected in 'zig-zag' fashion, stepping errors or stagger can sometimes arise. These occur because of a slight difference in the speed of walking on the forward and reverse traverses. The result is a staggered effect in the data, which is particularly noticeable on linear anomalies. This process corrects these errors.

Foerster cart system (MACS)

ealdec	This process decodes the raw data and converts it to a csv file. Positional values are assigned to each data point based on data from the GNSS and the offset of each sensor relative to the GNSS.
Ealmat.m	This is the equivalent of a zero mean traverse, wherein the data is normalised and a drift correction applied for each probe.
Ealgrid.m	This grids the data by merging each profile file. Parameters are set by based on the sensor spacing and resolution required.

Foerster cart system (MACS)

Zero Mean	This process sets the background mean of each traverse to zero. The operation
Traverse	removes striping effects and edge discontinuities caused by individual sensors having slightly different values when zeroed or where striping errors occur due to instrument drift or are a product of data collection.

Display

Greyscale plot	A greyscale plot of magnetic data is a visual representation of magnetic field strength variations over a given area. Magnetic gradient measurements are converted into a two-dimensional image where different shades of grey correspond to different magnetic values. This format divides a given range of readings into a set number of classes. Each class is represented by a specific shade of grey, the intensity increasing with value. All values above the given range are allocated the same shade (maximum intensity); similarly, all values below the given range are represented by the minimum intensity shade. In this instance black is used for the maximum intensity values and white for the minimum.
X-Y trace plot	An X-Y trace plot of magnetic data is a visual representation of magnetic field strength variations over a given area. Magnetic gradient measurements along a single traverse are displayed as a graph where the X-axis represents the distance along a traverse and the Y-axis is the measured magnetic gradient value at that point. Plots for each traverse are stacked to produce the X_Y trace plot for an area. The main advantage of the shape of individual anomalies can be viewed, and if required the full range of data can be viewed, although the data is often clipped at +/- 15 nT to +/- 20 nT.

Interpretation Categories

In certain circumstances (usually when there is corroborative evidence from desk-based or excavation data) very specific interpretations can be assigned to magnetic anomalies (for example, *Roman Road, Wall*, etc.) and where appropriate, such interpretations will be applied. The list below outlines the generic categories commonly used in the interpretation of the magnetic gradient data.

<i>Archaeology / probable archaeology</i>	This term is used when the form, nature and pattern of the responses are clearly or very probably archaeological and /or if corroborative evidence is available. These anomalies, whilst considered anthropogenic, could be of any age.
<i>Possible archaeology</i>	These anomalies exhibit either weak signal strength and / or poor definition, or form incomplete archaeological patterns, thereby reducing the level of confidence in the interpretation. Although the archaeological interpretation is favoured, they may be the result of variable soil depth or plough damage.
<i>Industrial / Burnt / fired</i>	Strong magnetic anomalies that, due to their shape and form or the context in which they are found, suggest the presence of kilns, ovens, corn dryers, metal- working areas or hearths. It should be noted that in many instances modern ferrous material can produce similar magnetic anomalies.
<i>Ridge and furrow</i>	Parallel linear anomalies whose broad spacing suggests ridge and furrow cultivation. In some cases, the response may be the result of more recent agricultural activity.
<i>Uncertain origin</i>	Anomalies which stand out from the background magnetic variation, yet whose form and lack of patterning gives little clue as to their origin. Often the characteristics and distribution of the responses straddle the categories of <i>Possible Archaeology / Natural</i> or (in the case of linear responses) <i>Possible Archaeology / Agriculture</i> ; occasionally they are simply of an unusual form.
<i>Former field boundary (probable and possible)</i>	Anomalies that correspond to former boundaries indicated on historic mapping, or which are clearly a continuation of existing land divisions. Possible denotes less confidence where the anomaly may not be shown on historic mapping but nevertheless the anomaly displays all the characteristics of a field boundary.
<i>Agriculture (ploughing)</i>	Parallel linear anomalies or trends with a narrower spacing, sometimes aligned with existing boundaries, indicating more recent cultivation regimes. The general orientation of the cultivation regime is shown but, for the sake of clarity, each individual anomaly has not been shown.
<i>Agriculture (land drain)</i>	Weakly magnetic linear anomalies, quite often appearing in series forming parallel and herringbone patterns. Smaller drains may lead and empty into larger diameter pipes, which in turn usually lead to local streams and ponds. These are indicative of clay fired land drains.
<i>Natural (e.g. geological / pedological)</i>	These responses form clear patterns in geographical zones where natural variations are known to produce significant magnetic distortions.
<i>Magnetic disturbance</i>	Areas of strong dipolar / bipolar anomalies, usually related to a spread / concentration of modern magnetic including ferrous and fired (e.g. brick or tile rubble) material.
<i>Service (e.g. pipe, cable or drain)</i>	Magnetically strong anomalies, usually forming linear alignments are indicative of ferrous pipes cables. Sometimes other materials (e.g. pvc) or the fill of the trench can cause weaker magnetic responses which can be identified from their uniform linearity.
<i>Ferrous</i>	This type of response is associated with ferrous material and may result from small items in the topsoil, larger buried objects such as pipes, or above ground features such as fence lines or pylons. Ferrous responses are usually regarded as modern. Individual burnt stones, fired bricks or igneous rocks can produce responses similar to ferrous material.

Where appropriate some anomalies will be further classified according to their form (positive or negative) and relative strength and coherence (trend: weak and poorly defined).

Appendix B - Technical information: Magnetic theory

Detailed magnetic survey can be used to effectively define areas of past human activity by mapping spatial variation and contrast in the magnetic properties of soil, subsoil and bedrock. Although the changes in the magnetic field resulting from differing features in the soil are usually weak, changes as small as 0.1 nanoTeslas (nT) in an overall field strength of 48,000 (nT), can be accurately detected.

Weakly magnetic iron minerals are always present within the soil and areas of enhancement relate to increases in *magnetic susceptibility* and permanently magnetised *thermoremanent* material.

Magnetic susceptibility relates to the induced magnetism of a material when in the presence of a magnetic field. This magnetism can be considered as effectively permanent as it exists within the Earth's magnetic field. Magnetic susceptibility can become enhanced due to burning, soil formation, weathering, erosion and complex biological or fermentation processes.

Thermoremanence is a permanent magnetism acquired by iron minerals that, after heating to a specific temperature known as the Curie Point, are effectively demagnetised followed by re-magnetisation by the Earth's magnetic field on cooling. Thermoremanent archaeological features can include hearths and kilns; material such as brick and tile may be magnetised through the same process.

Silting and deliberate infilling of ditches and pits with magnetically enhanced soil creates a relative contrast against the much lower levels of magnetism within the subsoil into which the feature is cut. Systematic mapping of magnetic anomalies will produce linear and discrete areas of enhancement allowing assessment and characterisation of subsurface features. Material such as subsoil and non-magnetic bedrock used to create former earthworks and walls may be mapped as areas of lower enhancement compared to surrounding soils.

A magnetic survey is carried out using a magnetometer which can measure these small changes in magnetic properties, which are referred to as anomalies. Magnetometers can either measure the total field or the gradient. Measuring the gradient of the earth's magnetic field can suppress any diurnal or regional effects and makes the instrument sensitive to smaller, localised anomalies, which is critical for archaeological surveys. The total field or magnetic gradient are measured in Tesla (T) with the small variations detected in archaeological surveys recorded in nanoTesla (nT).

Factors affecting the magnetic survey may include soil type, local geology, previous human activity and disturbance from modern services (pipes, cables or drains) or other modern material / activity.

Appendix C - OASIS Summary Sheet

OASIS Summary for sumogeop1-544112

OASIS ID (UID)	sumogeop1-544112
Project Name	Magnetometry Survey, Geophysical Survey at Augustus Way, Cheadle
Sitename	Augustus Way, Cheadle
Sitecode	28652
Project Identifier(s)	28652
Activity type	Magnetometry Survey, Geophysical Survey, MAGNETOMETRY SURVEY
Planning Id	
Reason For Investigation	Planning: Pre application
Organisation Responsible for work	SUMO Geophysics Ltd.
Project Dates	08-Jul-2026 - 09-Jul-2026
Location	Augustus Way, Cheadle NGR : SK 01835 42726 LL : 52.98187440385653, -1.974117360549289 12 Fig : 401835,342726
Administrative Areas	Country : England County/Local Authority : Staffordshire Local Authority District : Staffordshire Moorlands Parish : Cheadle
Project Methodology	Data was collected using a cart carrying four paired Bartington magnetic sensors. Four sensors mounted 1m horizontally apart and very accurately aligned to nullify the effects of the earth's magnetic field. Readings relate to the difference in localised magnetic anomalies compared with the general magnetic background. Each data point is geographically referenced using an on-board Trimble RTK survey grade GPS system. Readings were taken at 0.125m centres along traverses 1.0m apart. Readings relate to the difference in localised magnetic anomalies compared with the general magnetic background.
Project Results	The survey at Cheadle has not identified any anomalies of definite archaeological interest, apart from former ridge and furrow cultivation. Several responses of uncertain origin have been mapped, including discrete zones of magnetic disturbance which may reflect former quarrying activity. An old field boundary and areas of natural magnetic variations are also visible in the results.
Keywords	Ridge And Furrow - Uncertain - FISH Thesaurus of Monument Types Field Boundary - Uncertain - FISH Thesaurus of Monument Types
Funder	Private or public corporation Orion Heritage
HER	Staffordshire Historic Environment Record - unRev - STANDARD
Person Responsible for work	Rebecca Fradgley
HER Identifiers	
OASIS+ Geophysical survey	MAGNETOMETRY SURVEY - survey size: 6.30 hectares

Appendix D – Data Management Plan & Archive Selection Strategy

Data Management Plan

Project ID / OASIS Ref.

SUMO-28652 / sumoegeop1-544112

Project Name

Augustus Way, Cheadle

Project Description

Detailed magnetic survey over approximately 6.3 hectares at Cheadle.

Client

Orion Heritage

Project Manager

Rebecca Fradgley

Field Leader

Liam Brice-Bateman

Date DMP created

10.06.2026

Date DMP last updated

21.07.2026

Version

2

Technique - data

Detailed magnetic survey.

Manual – cart - other

Hand pushed system

Documentation and metadata

All documentation and data produced are stored on SUMO servers in a specific job file.

Data storage, access and back-up

- SUMO Secure server during the project life set up in a RAID configuration (a RAID configuration incorporates a level of data redundancy meaning if a single hard drive in fails data can still be restored).
- Snap shots of the data will be made at several intervals during the day to allow data to be restored for up to 30 days if changed / deleted.
- Once the final report has been completed data will be moved onto NAS drive set up in a RAID configuration.
- All data is backed up to an off-site location (Cloud storage).

Archive Selection Strategy

Digital Data

Selection

It is proposed that only the final version of all born digital documents (reports, images and CAD files) will be selected for inclusion in the Preserved Archive. All raw and processed survey data will be included in the preserved archive. Below is what will constitute the selected archive:

- Raw data in XYZ format .csv and .png plus .pgw world file
- Processed data as .png plus .pgw world file
- Final survey report .pdf
- CAD and Vector graphics (interpretations) in .dwg format

De-selected digital data

The de-selected material will be retained on the SUMO Secure server and Cloud storage.

Documents

Not applicable – no archive

Materials

Not applicable – no archive



- Archaeological Geophysics
- Engineering Geophysics
- Measured Building Services
- Utility and Topographic Services
- Aerial Surveys
- Rail Surveys

SUMO GeoSurveys is a trading name of SUMO Geophysics Ltd.
SUMO Services Ltd, incorporated under the laws of England and Wales,
Company Registration No.4275993.
Registered Office Unit 8 Hayward Business Centre, New Lane, Havant, Hampshire, PO9 2NL