

Evance R9000

5kW Wind Turbine

**Certified for
Feed-in Tariff**

- MCS approved product
- Eligible for Feed-in Tariffs
- Generates power continuously from 3m/s
- Reliability backed by millions of operating hours in the field
- Outstanding durability - minimal maintenance
- Low environmental impact - noise, visual & foundations
- Single or three phase connection
- On-grid & off-grid solutions
- Conforms to IEC 61400-2 international standard




The Evance R9000 small wind turbine is the result of years of dedicated research and development, based on engineering experience of designing big wind turbines.

Specifically designed to capture more energy at lower wind speeds, the R9000 is one of the most efficient small wind turbines available.

The R9000 already has several accreditations, including the UK MCS certification and USA SWCC conditional certification.

The efficient and reliable Evance R9000 is already enabling homes, farms and businesses around the world to reduce energy bills and carbon footprint.


Annual Energy Yield vs Annual Mean Wind Speed




Specification

Architecture	Upwind, 3 bladed rotor, self regulating
Rated Power	5kW @ 12m/s (26.9mph), continuous to 60m/s (134mph)
BWEA Reference Power	4628W (power output at 11m/s (24.6 mph))
Annual Energy Yield	8780kWh with Annual Mean Wind Speed (AMWS) of 5m/s (11.2mph) (to IEC & BWEA Standards)
Cut-In Wind Speed	3m/s (6.7mph)
Cut-Out Wind Speed	None - continuous generation to survival wind speed
Survival Wind Speed	60m/s (134mph)
IEC Turbine Class	Conforms to IEC 61400 to Class II - AMWS up to 8.5m/s (19mph)
Control System	Patented Reactive Pitch™ control
Rotor	Diameter: 5.5m (18') Speed: 200rpm nominal
Blade	Fully optimised aerofoil ensuring max yield & min noise. Low reflection, UV & anti-erosion coatings
Generator	Patented brushless direct drive, air-cored high efficiency Permanent Magnet Alternator
Gearbox	None required (see generator)
Emergency Braking	Patented automatic ElectroBrake™ (with manual control for servicing). No moving parts
Yaw Control	Passive tail vane and rotor
Tower	Free-standing monopole, hydraulic RAM or Gin pole tilt Heights: 10m, 12m, 15m & 18m (33', 40', 50' & 60')
Tower Foundation	Root, pad & rock options
Design Longevity	20 years minimum with regular service inspection
Noise	Lp, 25m = 53dB(A). BWEA Reference Sound Level at 8m/s (17.9mph) & 25m (82') distance Lp, 60m = 45.5dB(A). BWEA Reference Sound Level at 8m/s (17.9mph) & 60m (197') distance
Operating Temperature Range	-20°C - +50°C
Warranty	5 years (see Evance Terms & Conditions for details)

Average Power vs Wind Speed



Noise Levels



Evance Wind Turbines Ltd
Unit 6, Weldon Road, Loughborough, Leicestershire LE11 5RN United Kingdom

T: +44 (0)1509 215669
F: +44 (0)1509 267722
E: enquiries@evancewind.com
www.evancewind.com



Certificate Number MCS WT0039
Small Wind Turbine

We are continually improving our products and reserve the right to alter the above specifications at any time without notice.
All trademarks and registered trademarks used herein are the property of their respective owners.