

Sloping ceilings to roof slopes insulated with 100mm thickness of Kingspan Thermapitch TP10 rigid urethane insulation fitted between rafters and underside of rafters lined with Kingspan Kooltherm K18 insulated dry lining board 62.5mm thick, scrimmed and skimmed in 'Thistle' board finish plaster.

Supply and fit ridge mounted Glazelight by Skylight International, comprising triple glazed units fitted to powder coated aluminium frames on softwood framework all to manufacturer's details, complete with flashing including trimming openings in roof structure and plasterboard and skim finish to reveals. Height to top of rooflight not to exceed adjacent ridge height.

Roof covering to be of reclaimed Staffordshire blue plain tiles to match existing and to Conservation Officer's approval on 38 x 19 sawn battens, to 100mm gauge on layer of Kingspan 'nilvent' or similar approved breathable membrane.

ADUNALEUM

MR. & MRS. P. MARTIN

DATE October 14

PROPOSED REPLACEMENT ROOF COVERING SCALES: AT THE EAVES, SECTIONS EAVES LANE, CHEADLE, STOKE-ON-TRENT, STAFFS. ST10 2AG DRAWN BY MALCOLM SALES QUANTITY SURVEYORS, DESIGNERS AS PROPOSED & BUILDING COST CONSULTANTS CHURCHILL SUITE, DETAILS LULWORTH HOUSE, FOR APPLICATION FOR 51, HIGH STREET, CHEADLE, STOKE-ON-TRENT, STAFFS. ST10 1AR TEL: 01538 757233 MOB: 07889 225437

E-MAIL Malcolm.Sales@salesqs.co.uk

